


SCHWINGMETALL® Puffer



Puffer Typ C													
Abmessungen				Federsteifigkeiten			max. Belastungen			Masse	Elastomer Härte Shore A	Form-Nr.	Artikel-Nr.
d mm	h mm	l mm	g	C _x N/mm	C _y N/mm	C _z N/mm	F _x N	F _y N	F _z N	Stück kg			
13	26	5,0	M4	2	2	13	25	25	65	0,009	40	21887/C	3913402000
13	26	5,0	M4	3	3	25	27	27	80	0,009	55	21887/C	3913202000
13	26	5,0	M4	4	4	40	29	29	110	0,009	65	21887/C	3913102000
15	15	4,5	M4	13	13	68	35	35	90	0,007	40	25326/C	3913404000
15	15	4,5	M4	24	24	125	40	40	125	0,007	55	25326/C	3913204000
15	15	4,5	M4	37	37	190	43	43	160	0,007	65	25326/C	3913104000
20	25	6,0	M6	8	8	39	60	60	150	0,020	40	31658/C	3913406000
20	25	6,0	M6	14	14	73	65	65	180	0,020	55	31658/C	3913206000
20	25	6,0	M6	22	22	114	70	70	225	0,020	65	31658/C	3913106000
30	20	7,0	M8	30	30	230	150	150	400	0,042	40	25356/C	3913412000
30	20	7,0	M8	56	56	410	160	160	500	0,042	55	25356/C	3913212000
30	20	7,0	M8	87	87	626	170	170	650	0,042	65	25356/C	3913112000
30	30	7,0	M8	13	13	74	150	150	350	0,051	40	31660/C	3913413000
30	30	7,0	M8	24	24	139	160	160	420	0,051	55	31660/C	3913213000
30	30	7,0	M8	37	37	217	170	170	600	0,051	65	31660/C	3913113000
40	30	7,0	M8	29	29	189	250	250	630	0,072	40	20291/C	3913414000
40	30	7,0	M8	54	54	346	260	260	850	0,072	55	20291/C	3913214000
40	30	7,0	M8	83	83	533	270	270	1050	0,072	65	20291/C	3913114000
40	40	7,0	M8	14	14	89	250	250	600	0,090	40	27796/C	3913415000
40	40	7,0	M8	25	25	168	260	260	730	0,090	55	27796/C	3913215000
40	40	7,0	M8	39	39	263	270	270	890	0,090	65	27796/C	3913115000
50	45	8,8	M10	23	23	119	390	390	950	0,169	40	27797/C	3913419000
50	45	8,8	M10	42	42	228	410	410	1300	0,169	55	27797/C	3913219000
50	45	8,8	M10	65	65	358	430	430	1800	0,169	65	27797/C	3913119000
70	45	8,8	M10	71	71	529	750	750	1900	0,317	40	20290/C	3913420000
70	45	8,8	M10	132	132	953	790	790	2650	0,317	55	20290/C	3913220000
70	45	8,8	M10	207	207	1457	830	830	3600	0,317	65	20290/C	3913120000
75	55	11,5	M12	55	55	272	900	900	2200	0,455	40	25336/C	3913422000
75	55	11,5	M12	101	101	512	1000	1000	2950	0,455	55	25336/C	3913222000
75	55	11,5	M12	157	157	796	1050	1050	4050	0,455	65	25336/C	3913122000

Puffer Typ C													
Abmessungen				Federsteifigkeiten			max. Belastungen			Masse	Elastomer Härte Shore A	Form-Nr.	Artikel-Nr.
d mm	h mm	l mm	g	C _x N/mm	C _y N/mm	C _z N/mm	F _x N	F _y N	F _z N	Stück kg			
100	55	17,0	M16	103	103	561	1700	1700	4500	0,990	40	25335/C	3913425000
100	55	17,0	M16	191	191	1045	1900	1900	6200	0,990	55	25335/C	3913225000
100	55	17,0	M16	297	297	1619	2100	2100	8300	0,990	65	25335/C	3913125000
100	75	17,0	M16	53	53	279	1500	1500	4000	1,165	40	25328/C	3913426000
100	75	17,0	M16	96	96	540	1600	1600	5800	1,165	55	25328/C	3913226000
100	75	17,0	M16	149	149	848	1700	1700	7500	1,165	65	25328/C	3913126000
150	55	20,0	1)	216	216	1948	3500	3500	11000	2,500	40	31475/C	3913427000
150	55	20,0	1)	398	398	3511	3750	3750	16000	2,500	55	31475/C	3913227000
150	55	20,0	1)	621	621	5363	4000	4000	21000	2,500	65	31475/C	3913127000
150	75	20,0	1)	139	139	858	3500	3500	9500	2,950	40	25303/C	3913428000
150	75	20,0	1)	254	254	1613	3750	3750	14500	2,950	55	25303/C	3913228000
150	75	20,0	1)	395	395	2507	4000	4000	19000	2,950	65	25303/C	3913128000
200	100	20,0	1)	160	160	929	6000	6000	17500	5,920	40	25329/C	3913429000
200	100	20,0	1)	291	291	1802	6400	6400	25000	5,920	55	25329/C	3913229000
200	100	20,0	1)	451	451	2834	6800	6800	33500	5,920	65	25329/C	3913129000

1) geeignet für Gewinde bis M20; Butzendurchmesser 40 mm

Belastungsrichtungen

